



Specifications

General Description: Clear and White, soft, flexible vinyl with a clear permanent acrylic adhesive. Convex™ vinyls are intended to be used for thermal resin transfer printing and/or over-laminating. Please use Convex™ High-Bond Matte for ink jet printing.

Different combinations of Convex® or Pro-Shield™ laminates can be used to achieve a variety of decal thicknesses. Please see the disclaimer at the bottom.

Thickness	4 mil vinyl with 2 mil. of adhesive.
Outdoor Life	2 years, 6 years for matte, and 7 years for UV gloss
Shelf Life	2 years stored at 70° F & 50%RH
Adhesive Properties	2 mils. of permanent acrylic pressure sensitive adhesive works for most surfaces including textured low energy
Service Temperature Range	-40° F to 176° F
Minimum Application Temp.	50° F

Recommended Application Techniques: Prep molded plastic surfaces with acetone or alcohol to remove "mold release" and other contaminants from the surface. Apply dry or wet. High-Bond adhesive is not made for repositioning, so be sure to take care when applying.

All of the descriptive information listed above is our recommendation only. This information does not suggest or constitute a written or verbal warranty or guaranty of any kind by the manufacturer or distributor of this product. Purchasers of this product shall be responsible for independently determining the suitability of the material for the intended application.